



MAGIC

Engineered to delight!



MAGIC

SPECIFICATIONS

ENGINE	
Model	TATA 275 IDI NA
Engine Capacity / No. of Cyl	702 cc / 2 Cyl
Max. Output	16 Hp @ 3200 rpm
Max. Torque	38 Nm @ 2000 rpm
Emission	BS III / BS II / E II
CLUTCH	Single plate dry friction diaphragm type (170 diameter)
GEAR BOX	GBS 65
FRONT AXLE	Synchromesh (4 F + 1 R) Rigid beam construction
REAR AXLE	Single reduction, salisbury type with hypoid gears and semifloating axle shafts
STEERING	Mechanical, variable ratio (20.5 to 24.5), 380 mm diameter
SUSPENSION	
Туре	Parabolic leaf spring suspension at both front and rear
Shock Absorber	Hydraulic double-acting telescopic type
BRAKES	
Туре	Vaccum-assisted dual circuit hydraulically activated
Front	Disc brakes
Rear	Drum brakes (200 mm dia x 30 mm)
WHEELS & TYRES	
Tyres	145 R12 LT 8PR Radial

FUELTANK	30 Litres
DIMENSIONS (MM)	
Width (mm)	3790
Length (mm)	1500
Height (mm)	1845 (unladen)
Wheelbase (mm)	2100
Internal Length (mm)	2212
Internal Height (mm)	1326
Internal Width (mm)	1220
Ground Clearance (mm)	160
Front Track (mm)	1300
Rear Track (mm)	1320
Turning Radius	4.3 m
Floor Height	450 (laden) / 635 (unladen)
PERFORMANCE	
Max. Speed	64 kmph
Max. Gradeability	22%
Grade Restartability	21%
WEIGHTS (KGS)	
Kerb Weight	1000
Max. GVW	1600
CG From Ground (mm)	800 (laden)/ 635 (unladen)
SEATING CAPACITY	4+1 / 6+1 / 7+1

Available in Right Hand Drive & Left Hand Drive

TATA MOTORS LIMITED

International Business, A Block, Shivsagar Estate, Dr A B Road, Worli, Mumbai 400018. India.

Tel: 9122 67577200, Fax: 9122 67577225 Website: www.tatamotors.com